



“P” TYPE “J” COIL



DESCRIPTION

1/2 inch (13 mm) I.D. Coil.


FEATURES

One piece encapsulated design that is:



- Weatherproof (when applied with o-rings)
- No external metal shell

COIL SPECIFICATION



Wattage	21 Watts Nominal
Duty Rating	Continuous Duty ±10% rated voltage at 120°F (49°C) ambient
Min Current for Actuation	80% of rated current at room temperature
Magnet Wire Class	H or Better for all voltages
Temperature Range	-40 to 392 F (-40 to 200 C)
Encapsulation Material	Thermo-Plastic, resistant to moisture, caustic solutions, fungus, and vibrations





JA





JL




JJ



JD



JH



ORDERING INFORMATION

P	-	-		
TERMINATIONS				VOLTAGE
AMP Superseal - Integral	JA	12		12 VDC / 1.75 Amp
Double lead	JL	24		24 VDC / .875 Amp
AMP Jr. Timer - Integral	JJ			
Metri-Pack - Integral	JM			
Deutsch - Integral DT04-2P	JD			
DIN 43650 (Hirschmann)	JH			

Approximate Coil Weight: .43 lbs (.19 kg)

WARNING: the specifications/application data shown in our catalogs and data sheets are intended only as a general guide for the product described (herein). Any specific application should not be undertaken without independent study, evaluation, and testing for suitability.



4484 Boeing Drive Rockford, IL 61109 • USA • Phone +1 (815) 397-6628 • Fax +1 (815) 397-2526
 mail: delta@delta-power.com • www.delta-power.com



Via Malavolti, 36 • 41122 Modena • ITALY • Phone +39 (059) 254895 • Fax +39 (059) 253512
 mail: tecnord@tecnord.com • www.tecnord.com